



Product Service

# CERTIFICATE

No. Z2 021860 0208 Rev. 00

**Holder of Certificate:** **Ledon A/S**  
Vestergade 25  
Gram  
6510 Gram  
DENMARK

**Certification Mark:**



**Product:** **Swings**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713330926-01

**Valid until:** 2029-03-07

**Date,** 2024-04-09

( Tobias Hofmann )

# CERTIFICATE

No. Z2 021860 0208 Rev. 00

**Model(s):** 1149, 1169, 1169EXA, 1170, 1170EXA, 1171, 1171EXA, 1172, 1172EXA, 1174, 1174EXA, 1175, 1175EXA, 1176, 1179, 1179EXA, 1180, 1180EXA, 1181, 1181EXA, 1182, 1182EXA, 1185, 1185-0, 1185EXA, 1185EXA-0, 1186, 1186-0, 1186EXA, 1186EXA-0, 1187, 1187-0, 1187EXA, 1187EXA-0, 1188, 1188-0, 1188EXA, 1188EXA-0, 1189, 1189-0, 1189EXA, 1189EXA-0, 1190, 1190-0, 1190EXA, 1190EXA-0, 302230, LB1177, LB1178

## Parameters:

Swing frames made of galvanised steel pipes  $\varnothing$  76.1 x 2.9 mm.  
 Frames could be combined with the following swing seat models:  
 1110, 1112, 1114, 1115, 1035, 1036.  
 Model suffixes EXA, LB are decorative elements.

Model: dimensions (L x W x H); Possible swing seats

1149: 1.63 x 0.34 x 1.88 m; 1113  
 1169: 2.40 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114  
 1169EXA: 2.40 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114  
 1170: 3.50 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114  
 1170EXA: 3.34 x 2.27 x 2.43 m  
 1171: 2.40 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114  
 1171EXA: 2.23 x 2.27 x 2.43 m; 1110  
 1172: 3.50 x 2.70 x 2.20 m; 1110, 1112, 1113, 1114  
 1172EXA: 3.34 x 2.27 x 2.43 m; 1110  
 1174: 3.50 x 2.70 x 2.20 m; 1035, 1036  
 1174EXA: 3.34 x 2.27 x 2.43 m  
 1175: 3.50 x 2.70 x 2.20 m; 1035, 1036  
 1175EXA: 3.34 x 2.27 x 2.43 m, 1036  
 1176: 3.50 x 2.70 x 2.20 m; 1036  
 1179: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114  
 1179EXA: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114  
 1180: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114  
 1180EXA: 3.46 x 2.61 x 2.79 m; 1110  
 1181: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114  
 1181EXA: 2.36 x 2.61 x 2.79 m; 1110  
 1182: 3.85 x 2.90 x 2.50 m; 1110, 1112, 1113, 1114  
 1182EXA: 3.46 x 2.61 x 2.79 m; 1110  
 1185: 6.60 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114  
 1185-0: 6.60 x 2.30 x 2.20 m  
 1185EXA: 6.35 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114  
 1185EXA-0: 6.35 x 2.27 x 2.43 m  
 1186: 6.50 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114, 1035, 1036  
 1186-0: 6.50 x 2.30 x 2.20 m  
 1186EXA: 6.25 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114, 1036  
 1186EXA-0: 6.25 x 2.27 x 2.43 m  
 1187: 5.30 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114  
 1187-0: 5.30 x 2.30 x 2.20 m  
 1187EXA: 5.05 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114  
 1187EXA-0: 5.05 x 2.27 x 2.43 m  
 1188: 9.70 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114



# CERTIFICATE

No. Z2 021860 0208 Rev. 00

1188-0: 9.70 x 2.30 x 2.20 m  
 1188EXA: 9.37 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114  
 1188EXA-0: 9.37 x 2.27 x 2.43 m  
 1189: 6.35 x 2.30 x 2.20 m; 1035, 1036  
 1189-0: 6.35 x 2.30 x 2.20 m  
 1189EXA: 6.14 x 2.27 x 2.43 m; 1035, 1036  
 1189EXA-0: 6.14 x 2.27 x 2.43 m  
 1190: 8.30 x 2.30 x 2.20 m; 1110, 1112, 1113, 1114, 1035, 1036  
 1190-0: 8.30 x 2.30 x 2.20 m  
 1190EXA: 7.96 x 2.27 x 2.43 m; 1110, 1112, 1113, 1114, 1035, 1036  
 1190EXA-0: 7.96 x 2.27 x 2.43 m  
 302230: 3.50 x 2.70 x 2.20 m; 1110  
 LB1177: 2.40 x 2.70 x 2.20 m; 1115  
 LB1178: 3.50 x 2.70 x 2.20 m; 1115

**Tested according to:** EN 1176-1:2017  
 EN 1176-2:2017